

A-A

146

B

S

S+120-60

109

30-60

2

12

4

6

5



109

17

- 1-Water draining gutter
- 2-Polyurethane insulating wedge
- 3-Tile supporting profile
- 4-XDP FAKRO vapour permeable collar
- 5-Tress made of sheep wool FAKRO (XDP)
- 6-Blocks made of sheep wool FAKRO (XDP)
- 7-EZV FAKRO flashing upper element
- 8-XLW internal lining horizontal element
- 12-EZV FAKRO flashing side element
- 15-EZV FAKRO flashing lower element
- 17-Rafter
- 38-Installation bracket
- 109-XDS all-light flashing
- 146-FTS-V UZ pivot window FAKRO

FTS-V U2		
Frame width S[mm]	Frame height H[mm]	Window symbol
457	780	46
	980	48
	780	47
477	980	49
	780	01
	980	02
547	1180	16
	780	22
	980	03
	1180	04
657	1400	14
	780	23
	980	05
	1180	06
	1500	07
	1400	13
	780	24
	980	15
	1180	08
	1400	09
	1600	25
	780	20
	980	20
937	1180	10
	1400	11
	1600	50
	780	26
	980	12
	1180	18
	1400	17

FAKRO



15° - 90°

Vertical and horizontal cross-section:
FTS-V U2 roof window with EZV flashing for profiled roofing materials

FORMAT:
A4

SCALE:
1:1/0/1:5

DATE:
06.2011

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.